

AMENDMENTS TO THE CLAIMS

Please replace the pending claims with the following list of claims:

1. (Currently Amended) A method at a wireless mobile communication station for enabling the wireless mobile communication station to selectively permit desired packet data to be pushed from an originator of packet data to the wireless mobile communication station, the station being operatively associated with a wireless communication network providing packet data transferring services, the method comprising the acts of:

receiving at the wireless mobile communication station a network address of an originator of packet data that is attempting to push the packet data to the mobile communication station;

acquiring at the wireless mobile communication station an identity corresponding to the received network address;

determining at the wireless mobile communication station, based upon the identity, whether or not packet data reception from said originator is desired; and

establishing at the wireless mobile communication station, ~~if only after~~ it is determined that the packet data reception from said originator is desired, a packet data session with said originator,

thereby ~~facilitating~~ enabling the wireless mobile communication station to selectively permit desired packet data to be pushed from said originator to the wireless mobile communication station.

2. (Previously Presented) The method as claimed in claim 1, wherein said determining act includes:

displaying said identity on displaying means associated with the wireless mobile communication station; and

accepting, from a user of the wireless station, either a confirmation or a rejection regarding reception of packet data from said originator having the displayed identity.

3. (Original) The method as claimed in claim 1, wherein said acquiring act includes:
establishing a packet data session with an address translation server; and
requesting translation of the network address to the corresponding identity.
4. (Original) The method as claimed in claim 1, wherein said network address of said receiving act is received in a short message, the short message being received from a short message service provided by said wireless communication network.
5. (Previously Presented) The method as claimed in claim 1, wherein establishing a packet data session with the originator includes establishing a packet data session using the received network address.
6. (Original) The method as claimed in claim 1, wherein said network address is an Internet Protocol address.
7. (Original) The method as claimed in claim 1, wherein said act of establishing a packet data session with the originator includes establishing a packet data session using said identity.
8. (Original) The method as claimed in claim 1, wherein said identity is a network server name.
9. (Original) The method as claimed in claim 8, wherein said network server name is an Internet domain host name of a network server.
10. (Previously Presented) The method as claimed in claim 1, further including:
receiving a first originator identification code in said act of receiving a network address of an originator of packet data;
receiving a second originator identification code over the packet data session established with the originator; and

verifying, based on a comparison between the first and the second identification code, that the packet data session was established with the originator of the received network address.

11. (Previously Presented) A computer-readable medium storing computer-executable components for causing a wireless mobile communication station to perform the method recited in claim 1 when the computer-executable components are run on a microprocessor included by a wireless mobile communication station.

12. (Previously Presented) A wireless mobile communication station arranged to be operatively associated with a wireless communication network providing packet data transferring services, wherein the wireless mobile communication station includes processing means, memory means, interface circuitry means and user interface means for performing the method recited in claim 1, thereby facilitating desired packet data to be pushed from an originator to the wireless mobile communication station.

13. (Currently Amended) A method of a system which includes a wireless mobile communication station and an originator of information for enabling the wireless mobile communication station to selectively permit desired packet data to be pushed from the originator to the wireless mobile communication station, the wireless mobile communication station being operatively associated with a wireless communication network providing packet data transferring services, the method comprising the acts of:

transmitting, to the wireless mobile communication station, from ~~the an~~ originator that is attempting to push the packet data to the mobile communication station to the wireless mobile communication station, the originator's own network address;

determining, at the wireless mobile communication station and based upon an identity corresponding to the received network address, whether or not packet data reception from said originator is desired; and

establishing, from the wireless mobile communication station, only after ~~if~~ it is determined that the packet data reception from said originator is desired, a packet data session with said originator,

thereby enabling the wireless mobile communication station to selectively permit ~~facilitating~~ desired packet data to be pushed from said originator to the wireless mobile communication station.

14. (Previously Presented) The method as claimed in claim 13, wherein said determining act includes:

displaying said identity on displaying means associated with the wireless mobile communication station; and

accepting, from a user of the wireless mobile communication station, either a confirmation or a rejection regarding reception of packet data from said originator having the displayed identity.

15. (Previously Presented) The method as claimed in claim 13, wherein said identity is acquired by the wireless mobile communication station by performing the acts of:

establishing, from the wireless mobile communication station, a packet data session with an address translation server; and
requesting translation of the network address to the corresponding identity.

16. (Previously Presented) The method as claimed in claim 13, wherein said originator's network address of said transmitting act is transmitted by requesting a short message service provided by a wireless communication network to transmit a short message that includes said network address to the wireless mobile communication station.

17. (Previously Presented) The method as claimed in claim 13, wherein said act of establishing a packet data session with the originator includes establishing a packet data session using the originator's network address.

18. (Previously Presented) The method as claimed in claim 13, wherein said network address is an Internet Protocol address.

19. (Original) The method as claimed in claim 13, wherein said act of establishing a packet data session with the originator includes establishing a packet data session using said identity.

20. (Original) The method as claimed in claim 13, wherein said identity is a network server name.

21. (Original) The method as claimed in claim 20, wherein said network server name is an Internet domain host name of a network server.

22. (Previously Presented) The method as claimed in claim 13, further including:
transmitting a first originator identification code in said act of transmitting the originator's own network address;

transmitting, from the originator, a second originator identification code over the packet data session established between the wireless mobile communication station and the originator; and

verifying, at the wireless mobile communication station, and based on a comparison between the first and the second identification code codes, that the packet data session was established with the originator of the network address received in said act of transmitting the originator's own network address.

23. (Previously Presented) A system including a wireless mobile communication station and at least one originator server, the station being operatively associated with a wireless communication network providing packet data transferring services, wherein the system is arranged to perform the method recited in claim 13, thereby facilitating desired packet data to be pushed from the originator to the wireless mobile communication station.